

10 AUTOGAS PUMPS & MOTOR PACKAGES

FOR SINGLE PHASE ELECTRICAL SUPPLY

	MAX FLOW @ 0 PSID	COMPARATIVE FLOW @140 PSID	COMPARATIVE FLOW @ MAX DIFF.	MAX DIFFERENTIAL CAPABILITY
BLACKMER				
LGL154A-F + EMC-3 + VFD or Manual or Magnetic Starter (see pg 11) + Bypass (ME840-8-150)	11 GPM	8.5 GPM	8.5 GPM	140 PSID
LGL156A-F + EMC-5 + VFD or Manual or Magnetic Starter (see pg 11) + Bypass (ME840-8-225)	21 GPM	15.5 GPM	15 GPM	160 PSID
LGL158B-F + EMC 7.5 + VFD or Manual or Magnetic Starter (see pg 11) + Bypass (ME840-8-225)	32 GPM	25 GPM	22.5 GPM	200 PSID

CORKEN

HDPDLF060-1P53 (Includes motor, pump, bypass & VFD)	22 GPM	9.5 GPM	8 GPM	150 PSID
HDPDLF075-1P75 (Includes motor, pump, bypass & VFD)	40 GPM	22 GPM	14 GPM	200 PSID
HDPDLF-150-1P10 (Includes motor, pump, bypass & VFD)	58 GPM	34 GPM	17 GPM	250 PSID

SMITH PRECISION

GC-1ZL Complete pump/motor	13 GPM	7.5 GPM @ 125	–	125 PSID
----------------------------	--------	---------------	---	----------

FOR THREE PHASE ELECTRICAL SUPPLY

	MAX FLOW @ 0 PSID	COMPARATIVE FLOW @140 PSID	COMPARATIVE FLOW @ MAX DIFF.	MAX DIFFERENTIAL CAPABILITY
BLACKMER				
LGL154A-F + EMC-3 + VFD or Manual or Magnetic Starter + Bypass (ME840-8-150)	11 GPM	8.5 GPM	8.5 GPM	140 PSID
LGL156A-F + EMC-5 + VFD or Manual or Magnetic Starter + Bypass (ME840-8-225)	21 GPM	15.5 GPM	15 GPM	160 PSID
LGL158B-F + EMC 7.5 + VFD or Manual or Magnetic Starter + Bypass (ME840-8-225)	32 GPM	25 GPM	22.5 GPM	200 PSID

CORKEN

HDPDLF060-3P53 + VFD or Manual or Magnetic Starter (incl. pump, motor, & bypass)	22 GPM	9.5 GPM	8 GPM	150 PSID
HDPDLF075-3P75 + VFD or Manual or Magnetic Starter (incl. pump, motor, & bypass)	40 GPM	22 GPM	14 GPM	200 PSID
HDPDLF-150-3P10 + VFD or Manual or Magnetic Starter (incl. pump, motor, & bypass)	58 GPM	34 GPM	17 GPM	250 PSID

SMITH PRECISION

No offering for three phase applications.

- Units shown above are most often used configurations.
- Pump/Motor packages can be modified to suit a unique application if necessary.

Corken Pump Package Note: Bypass valve included in pump/motor packages have a 150 PSI Max Differential. If differential pressures up to 225 PSI are needed, order RMI Part Number ME840-8-225 for correct bypass valve.